

CCTV Kit

1 x DVR

1080P H.265+/H.265

4 x dome camera

1080P 2.8 mm



CAMERA SHOP 24

# Specifications

## Video recorder

<b>Video format</b>	HDTV / HDCVI / AHD / CVBS / IP
<b>Video inputs</b>	4 Channels BNC, (HDTV / HDCVI / AHD / CVBS)
<b>Hybrid configuration</b>	4 Channels from BNC and 1 Channel IP (4Mpx)
<b>Video outputs</b>	1 HDMI Full HD, 1 VGA, 1 BNC (CVBS) Independent
<b>Audio inputs</b>	1 Channel RCA
<b>Audio outputs</b>	1 Channel RCA
<b>Bidirectional audio</b>	Reusing the audio input/output
<b>Video / audio compression</b>	H.265+ / H.265 / H.264+ / H.264 / G.711u
<b>Display resolution</b>	1920x1080, 1280x1024, 1280x720, 1024x768
<b>Recording resolution</b>	4Mpx Lite HDTV / 1080p / 1080p Lite / 720p / WD1 / 4CIF / VGA / CIF
<b>Main Stream coding</b>	4Mpx Lite HDTV / 1080p (12 FPS) / 1080p Lite / 720p / VGA / WD1 / 4CIF / CIF (25 FPS)
<b>Extra Stream coding</b>	WD1 / 4CIF (12FPS) / CIF (25 FPS)
<b>Simultaneous multifunction</b>	Pentaplex: Live, Recording, Playback, Backup and Remote Access
<b>Alarms</b>	4 inputs / 1 relay
<b>Video analysis</b>	VCA: Tripwire   Area intrusion   Audio exception
<b>Recording method</b>	Manual, programmed, motion detection, alarm
<b>Backup</b>	USB (Memory, HDD, CD-RW, DVR-RW) / Network
<b>Internal memory</b>	1 HDD SATA 3.5" of up to 6TB (not included)
<b>Communication</b>	RS485 (PTZ) / 2 x USB (Mouse and backup) / Remote control / RJ45 (Ethernet)
<b>Remote access</b>	Web browser, Smartphone App and Safire Control Center CMS Software
<b>Power supply</b>	DC 12 V / 1.5 A
<b>Dimensions / Weight</b>	45 (He) x 315 (Wi) x 242 (De) mm / 2.0 Kg

## Cameras

Range	1080p ECO
Image sensor	High Performance CMOS
Resolution	HD 1080p (1920x1080) at 25 FPS
Video output	1 x BNC switchable between HDTV / HDCVI / AHD / CVBS
Minimum illumination	0 Lux / IR LEDs (40 m)
Basic functions	OSD menu (remote), Day/Night with IR-CUT (ICR)
Configurable OSD functions	Smart IR, 2D-NR, AE, AWB, AGC
Lens	2.8 mm (103°)
Power supply	DC 12 V / 300 mA
Degree of protection	Weatherproof IP66
Temp. operation	-40° C ~ 60° C
Dimensions	93 (He) x 110 (Ø) mm
Weight	340 g