

# XS-IPPT470-5ESW-FC-AI2

X-Security PT IP Camera

5 Megapixel (2560 × 1920)

1/2.8" CMOS | Fixed Lens 4mm

Human detection with active  
deterrence

Dual Light: IR and White Light 30m

WiFi (IEEE802.11b/g)



X-Security

PT IP camera

1/2.8" STARVIS™ CMOS

5 Megapixel Fixed lens 4mm

Full-Color

WiFi 2,4 GHz

Dual light: IR and white light up to 30m

Sound and light alarm

DWDR

3DNR

Bidirectional audio

Built-in microphone and speaker

MicroSD card recording up to 512GB

Human detection with active deterrence

Average speed 62º/segundo

H.265+

RJ-45 10/100 BaseT

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Weatherproof IP66

# Specifications

Brand	X-Security
Image sensor	1/2.8" STARVIS CMOS
Maximum resolution	5 Megapixel (2560 × 1920)
Lens	4 mm
Full-Colour	Yes
Main Stream rate	5M(1–20 fps),4M/1080p/1.3M/720p (1–25/30 fps)
Compression	D1/CIF (1–25/30 fps)
Minimum illumination	Color: 0.05 lux@F2.0 B/W: 0.005 lux@F2.0 0 lux (IR/white light on)
IVS	Tripwire; intrusion
Human detection	Yes
Image improvements	DWDR, BLC, HLC, AWB, AGC, 3D-NR, IVS, ROI, Privacy Masking
Day / Night	Removable mechanical ICR filter
Active Deterrence	White light warning, Sound warning alarm, sound warning alarm
Network interface	Wi-Fi 2,4 GHz (IEEE802.11n/b/g) / Ethernet RJ-45 (10Base-T/100Base-TX)
Internal memory	Slot for MicroSD Card, Max 512GB
Audio	Built-in speaker and microphone
Audio Compression	PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1
Audio I/O	1/1
Remote access	Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR
Interoperability	ONVIF
Power	DC 12 V / 1,5 A
Temp. operation	-30° C ~ +60° C
Degree of protection	Waterproof IP66, TVS 2000 V lightning proof; overvoltage protection; transient voltage protection
Dimensions	711 (mm) × 140.5 (mm)
Weight	0,5 Kg