

DAHUA-4070

DH-HAC-HFW1200RP-Z-A-2712-S6



4 in 1 2MP outdoor camera



- Dahua 4 in 1 camera
- 2MP@25/30ips
- Switchable 4 in 1 output
- ICR, 0.01/0.001 lux, Smart IR 80m
- 2.7~12 mm motorized optics
- Manual focus
- Digital WDR
- IP67 protection, basic anti-corrosion, 3AXIS.



Reference / Model

DAHUA-4070 / DH-HAC-HFW1200RP-Z-A-2712-S6

2 megapixel CMOS sensor

Digital resolution: 1080P (1920x1080), 960H (960x576)

Frames per second: 25/30 fps @1080P (CVI/TVI/AHD)

4-in-1 switchable output

Day/night mode with removable mechanical filter

0.01 lux F1.6 (color) / 0.001 lux F1.6 (B/W) / 0 lux IR On

Smart IR: 4 IR leds, 80 meters

2.7 ~ 12 mm motorized optics (no autofocus)

Angle of view: 28.3°~98.2°(H), 15.8°~51.9°(V), 32.1°~116.7°(D)

Image modes: BLC, HLC, Digital WDR, 3D-NR, Mirror.

Auto white balance

Auto gain control

Supports 8-zone privacy mask

DAHUA-4070

DH-HAC-HFW1200RP-Z-A-2712-S6



4 in 1 2MP outdoor camera

Reference / Model	DAHUA-4070 / DH-HAC-HFW1200RP-Z-A-2712-S6
Power supply: 12V DC ($\pm 30\%$)	
Power consumption: 9.4W (max.)	
Storage temperature: $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$)	
Operating temperature: $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$)	
Relative humidity: $<95\%$ (non-condensing)	
IP67 degree of protection	
Basic corrosion protection	
Metal housing	
Dimensions: 90.4 (W) x 90.4 (H) x 209.6 mm (W x H) x 209.6 mm (1.5 x 2.6 in)	
Gross weight: 760 g	
Net weight: 550 g	
3AXIS: $0^{\circ} \sim 360^{\circ}$ (PAN), $0^{\circ} \sim 90^{\circ}$ (TILT), $0^{\circ} \sim 360^{\circ}$ (Rotation)	