

# HAP120

BRANDED



## Features

---

- Branded
- External, Omnidirectional, Microphone
- Audio output via female RCA connector
- Power supply DC12V by male jack connector
- S/N ratio 58 dB
- Sensitivity -34dB
- Range 10~70 m2
- Output impedance 600 ?

# Specifications

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Coverage                           | 10 ~70 m2                         |
| Sensitivity                        | -34 dB                            |
| Frequency response                 | 80 Hz ~ 16 KHz                    |
| Directionality Pattern             | Omnidirectional                   |
| Signal-to-noise ratio              | SNR 58 dB (re 94dBSPL = 1Pa@1KHz) |
| Dynamic range                      | 74 dB                             |
| Maximum sustainable sound pressure | 110 dBSPL (1KHz, THD 1%)          |
| Output Impedance                   | 600 ohm (unbalanced)              |
| Signal Output                      | 2.5 Vpp / 88dBSPL                 |
| Microphone Type                    | Film condenser                    |
| Power supply                       | DC12V / 40 mA                     |
| Working temperature                | -30° C ~+70° C                    |
| Material                           | Aluminium                         |
| Weight                             | 48 g                              |
| Dimensions                         | 20 (H) x 40 (Ø) mm                |