

PTZ7212 – 2 Megapixel IP speed dome camera Dahua OEM

2 Megapixel PTZ IP Camera

1/2.8" STARVIS CMOS

Compression

H.264/H.264+/H.265/H.265+

5.1~61.2mm Varifocal lens

WEB, DSS/PSS, smartphone and NVR



Specifications

Image Sensor	1/2.8" STARVIS CMOS
Resolution	1080p(1920x1080), 720p(1280x720), D1(704x576), CIF(352x288)
Compression	H.264/H.264+/H.265/H.265+ (video), G711a / G771u (audio)
Main Stream rate	1080p (1~25 FPS) / 720p (1~50 FPS)
Extra Stream rate	D1 / CIF (1~25 FPS)
Bitrate	448 Kbps ~ 8 Mbps
Lens	Varifocal 5.1 ~ 61.2mm (Optical zoom 12x) Auto iris
Digital zoom	16x
Image improvements	WDR (120dB), 3DNR, HLC, BLC, ATW, AGC, Privacy Mask
Minimum illumination	0.005 Lux (Colour) / 0.0005 Lux (B/N)
Day / Night	Removable mechanical IRC filter
Network interface	Ethernet 10/100 BaseT
Remote access	WEB interface, CMS software, mobile application and NVR
Memory	Slot for MicroSD card (Max. 128GB)
Pan/Tilt range	Horizontal: 0° ~ 360°, Vertical: -2° ~ 90° auto flip: 180°
Manual speed	Horizontal: 0.1° ~ 300° /s, Vertical: 0.1° ~ 120° /s
Speed between presets	Horizontal: 300° /s, Vertical: 200° /s
Preset positions	300, 5 auto patterns, 8 auto tour, 5 auto scan
Communication	DH-SIP, ONVIF Compatible
Alarms	2 inputs / 1 relay NO/NC
Audio	1 input (Line In) / 1 output (Line Out)
Power supply	AC 24V / 1.5A, PoE IEEE802.3at
Degree of protection	Weatherproof IP66, Anti-vandal IK10
Temp. operation	-40°C ~ 60°C
Dimensions / Weight	234mm (H) x 186mm (∅)