

# DASHCAM-2M-IA-4G



## Features

---

- DASHCAM with AI for parking
- Double lens 3Mpx
- Intercom mode from APP
- Human and vibration detection
- Simple OBD connection
- Paid cloud storage
- GPS, 4G and built-in accelerometer

## Specifications

---

<b>Format</b>	Dashcam for front window
<b>Colour</b>	Matte black
<b>Antenna</b>	Internal
<b>Material</b>	ABS
<b>Protection</b>	Indoor camera
<b>Dimensions</b>	120mm x 46mm x 95mm
<b>Chipset</b>	T32ZN
<b>Detection range</b>	Front - 3 meters 90 degrees Back - 5 meters 90 degrees
<b>Sensitivity</b>	low, medium and high
<b>Optics</b>	front camera - 2.95mm, 2.0 opening rear camera - 2.28mm, 2.2 opening
<b>Viewing Angle</b>	Front camera: D: 122° * H: = 102,5° * V: 57° Rear camera: D: 170,2° * H: = 144,2° * V: 77,6°
<b>Sensor type</b>	SC235HAI (progressive scan CMOS of 2 MP and 1/2,9")
<b>Resolution</b>	2304 x 1296 pixels
<b>Night mink</b>	Front camera: None Rear camera: 3 m distance (940 nm)
<b>Sensitivity</b>	Ø3?550nm
<b>Threshold</b>	color to B/W - 0.8lux B/W to color - 8.5lux
<b>LED indicators</b>	Working mode - red and blue Coverage - blue Privacy - green
<b>Microphone</b>	Sensitivity: ?-38±3dBm with noise cancellation
<b>Speaker</b>	Built-in 8?/1W, Indication tone 75dB to 0,5 m
<b>SIM card</b>	Nano SIM
<b>Storage</b>	Up to 128Gb
<b>Buttons</b>	Reset, Power, Private Mode
<b>Power</b>	OBD cable
<b>Maximum consumption</b>	900mA

<b>Standby consumption</b>	2.5mA
<b>Consumption in work</b>	500mA
<b>Module 4G</b>	A7670E PN: S2-10D9P / Dimensions: 24*24 mm
<b>Standard 4G</b>	SIMCom LTE module Cat1
<b>Type of network</b>	LTE-FDD/LTE-TDD
<b>Compatible bands</b>	B1/B3/B5/B7/B8/B20
<b>Data flow</b>	Maximum downstream speed: 10 Mbps Maximum upload speed: 5 Mbps
<b>Audio Compression</b>	AAC?G.726
<b>Video compression</b>	H265
<b>Photograms</b>	15 FPS
<b>APP</b>	UBOX: Android 4.3 or higher IOS 9.X or higher
<b>Languages</b>	Chinese, English, French, German, German, Italian, Spanish, Japanese
<b>Simultaneous users</b>	Up to 3 users
<b>Matched</b>	Through QR code
<b>Pre-alarm recording</b>	5, 10 20 seconds
<b>OBD cable length</b>	3 meters
<b>Temperature withstand</b>	In operation: -20 ~ 60 ?, humidity <95 % Almacenamiento: -25 ~ 65 ?, humedad <95 %