

HWI-D121H-M

Hikvision IP Camera 2 MP

1/2.8" Progressive Scan CMOS

Compression H.265

2.8 mm Lens

EXIR IR LEDs range 30 m

Metal housing / IK10



Hikvision

IP camera

1/2.8" Progressive Scan CMOS

2 Megapixel (1920x1080)

Codificación H.265+/H.264+/H.265/H.264

2.8 mm Lens

0 Lux

IR Range 30 m

H.265

Dual stream

RJ-45 10/100 BaseT

PoE IEEE802.3af

Weatherproof IP67

Vandal proof IK10

Housing made of metal

IR Cut

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	1080p / 720p (25 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.264+/H.265/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Minimum illumination	Colour 0.01 Lux @ F1.2 Colour 0.028 Lux @ F2.0
Infrared lighting	0 Lux / EXIR LEDs IR (30 m)
Image improvements	DWDR, BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	No
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 400 mA, PoE IEEE802.3af
Degree of protection	Waterproof IP67 / Anti-vandal IK10
Material	Metallic
Temp. operation	-30° C ~ +50° C
Dimensions	186.3 mm (D) x 70 (Ø) mm
Weight	270 g