

iDS-7204HQHI-K1/2S

5n1 Hikvision recorder
4 CH HDTV I / HDCVI / AHD / CVBS /
2 IP
H.265 Pro+
HDMI & VGA Output
2 CH Artificial Intelligence
Supports 1 hard disk



Hikvision
DVR 5n1
4 CH video HDTV I/HDCVI/AHD/CVBS / 6 IP / 1 CH audio
H.265 Pro+/H.265+/H.265
Resolution per channel: 4Mpx Lite / 3Mpx / 1080p (15FPS)
Acusense, false alarm filter for vehicles and persons (2Ch)
HDMI Full HD, VGA & CVBS Outputs
PTZ Control (RS485/Coaxial)
Remote control
Mouse
Space for 1 HDD

Specifications

| | |
|----------------------------|--|
| Brand | HIKVISION |
| Video format | HDTV / HDCVI / AHD / CVBS / IP |
| Video inputs | 4 Channels BNC, (HDTV / HDCVI / AHD / CVBS) |
| Hybrid configuration | Up to 6 IP Channels (6Mpx), replacing all the BNC channels |
| Video outputs | 1 HDMI Full HD, 1 VGA, 1 BNC (CVBS) Independent |
| Audio inputs | 1 Channel RCA |
| Audio outputs | 1 Channel RCA |
| Bidirectional audio | Reusing the audio input |
| Audio Bit Rate | 64 Kbps |
| Audio compression | G.711u |
| Video compression | H.265 Pro+ / H.265 Pro / H.265 / H.264+ / H.264 |
| Display resolution | 1920x1080, 1280x1024, 1280x720, 1024x768 (60 Hz) |
| Recording resolution | 4Mpx Lite HDTV / 1080p / 1080p Lite / 720p / WD1 / 4CIF / VGA / CIF |
| Main Stream coding | 4Mpx Lite HDTV (15 FPS) / 1080p Lite / 720p / VGA / WD1 / 4CIF / CIF (25 FPS) |
| Extra Stream coding | WD1 / 4CIF (12FPS) / CIF (25 FPS) |
| Video Bit Rate | 32 Kbps at 6 Mbps |
| Simultaneous multifunction | Pentaplex: Live, Recording, Playback, Backup and Remote Access |
| Alarms | No |
| Artificial intelligence | Behavior detection of people and vehicles to filter false alarms, available in up to 2ch coaxial video |
| Recording method | Manual, programmed, motion detection |
| Backup | USB (Memory, HDD, CD-RW, DVR-RW) / Network |
| Internal memory | 1 SATA HDD 3.5" of up to 10 TB (not included) |
| Communication | 2 x USB (Mouse and backup) / Remote control / RJ45 (Ethernet) / RS-485 half-duplex |
| Remote connections | 32 |
| Remote access | Web browser, Smartphone App and Safire Control Center CMS Software |
| Power | DC 12V / 10W |
| Operating temperature | -10° ~ +55° C |
| Dimensions / Weight | 45 (H) x 315 (W) x 242 (D) mm / 1.16 Kg |