

XS-IPSD7525ISWHTA-8U-AI



PTZ X-Security 8 Mpx Ultra Range IP
Camera
Autotracking / Face detection
Compression H.265+
5.4-135mm (X25) Vari-focal lens
Audio / High speed 400°/segundo
WizSense: False alarm filter



X-Security
PTZ IP Camera
Ultra Range
High speed 400°/segundo
25X Optical zoom
1/2.8" Sony STARVIS™ CMOS Starlight
8 Megapixel (3840x2160)
5.4~135 mm Varifocal lens
High sensitivity Starlight
0.005 Lux
IR Range 150 m
Compression H.265+/H.265/H.264+/H.264/MJPEG
RJ-45 10/100 BaseT
PoE+ 802.3at
Weatherproof IP67, Anti-vandal IK10
Audio
IR Cut
Alarms
Intelligent functions
WizSense: False alarm filter for people and vehicles
Autotracking and face detection
SD card recording
WEB, CMS (DSS/PSS), Smartphone and NVR interface
ONVIF Compatible
Wall bracket included

Specifications

Brand	X-Security
Image sensor	1/1.8" STARVIS™ CMOS
Resolution	4K (3840 × 2160); 1080P (1920 × 1080); 1.3M (1280x 960); 720P (1280 × 720); D1 (704 × 576); CIF (352 × 288)
Compression	H.265+/H.265/H.264+/H.264/MJPEG (sub stream)
Main Stream rate	8M / 1080P / 1.3M / 720P (1–25/30 fps)
Extra Stream rate	2°: D1 / CIF (1–25/30 fps), 3°:1080P / 1.3M / 720P / D1 / CIF (1–25/30 fps)
Bitrate	H.265/H.264: 32 kbps–8192 kbps
Lens	Varifocal 5.4 ~ 135 mm (Optical zoom 25X) Auto Iris, Auto Focus
Digital zoom	x16
Image improvements	WDR (120dB),2D/ 3DNR, HLC, BLC, ATW, AGC, Privacy Mask
Minimum illumination	0.005 Lux (Colour) / 0.0005 Lux (B/W)
Infrared lighting	0 Lux @ 150m range
Day / Night	Removable mechanical ICR filter
Intelligent functions	Autotracking, face detection, line crossing, abandoned object, intrusion, false alarm filtering for humans and vehicles
Audio	1 input (Line In) / 1 output (Line Out)
Alarms	2 inputs / 1 relay
Network interface	Ethernet 10/100 BaseT
Remote access	WEB interface, CMS software, mobile application and NVR
Memory	Slot for Micro SD card (Max 256 GB)
Pan/Tilt Range	Horizontal: 0°~360°, Vertical: -15°~90° auto flip 180°
Manual speed	Horizontal: 0.1°~300° /s, Vertical: 0.1°~200° /s
Speed between Presets	Horizontal: 400° /s, Vertical: 300° /s
Preset positions	300, 5 auto pattern, 8 auto tour, 5 auto scan
Communication	DH-SD, ONVIF Compatible
Power	AC 24 V / 3 A , PoE+(802.3at)
Degree of protection	Weatherproof IP67, Anti-vandal IK10
Temp. operation	-40° C ~ +70° C
Dimensions	332 mm (H) x 190 (Ø) mm
Weight	4700 g