



SPECIFICATION

| | |
|-------------------------|---|
| Model NO. | MAMM1 |
| Camera | |
| Image Sensor | 1/3" Progressive Scan CMOS Sensor |
| Resolution | 4MP |
| Effective Pixels | 2560(H)*1440(V) |
| Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI |
| Audio Compression | G711A/U,AAC |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: 1/3-1/100000Sec |
| Minimum Illumination | Color: 0.01 Lux @ (F1.6, AGC ON) |
| S/N Ratio | 60dB |
| Scanning System | Progressive |
| Video Output | Network |
| Reset Button | Support |
| Lens | |
| Focus Length | Board Lens 3.7mm/F2.8 |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Pixels | 4Mp |
| Night Vision | |
| Infrared LED | N/A |
| Infrared Distance | N/A |
| IR Status | N/A |
| IR Power On | N/A |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Wireless | N/A |
| Protocol | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP |
| ONVIF | Support ONVIF 19.12(Profile S/T/G) |
| P2P | YES |
| POE | (External POE But Without Audio and Alarm Functions), Support IEEE 802.3af |
| Video Delay | 0.3S (Within the Lan) |
| Main Stream 1 | 2688*1512@20fps |

| | |
|---------------|---|
| Main Stream 2 | 2560*1440@30fps |
| Main Stream 3 | 1920*1080@30fps 1280*720@30fps |
| Sub Stream 1 | 1280*720@30fps |
| Sub Stream 2 | 720*480@30fps |
| Sub Stream 3 | N/A |
| Tri Stream | N/A |
| IE Brower | IE8-11, Google Chrome, Firefox , Mac Safari |
| Smart Phone | iPhone, Android |

| | |
|----------------------|--|
| AI Function | |
| Intelligent Analysis | Intrusion Detetion,motion detection based on human detection |

| | |
|------------------------|--|
| Camera Features | |
| Day/Night | Color |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion |
| Full Color | Support |
| Corridor Pattern | Support |
| Defog Mode | Support |
| ROI | Support |
| BLC | Support |
| WDR | 120dB |
| Motion Detection | Support(support enable the detection based on human movement only) |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/CMS/Web |
| Language | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese |

| | |
|------------------|---------------------------------|
| Interface | |
| Audio | 1 Built-in MIC |
| Alarm | N/A |
| SD Card Slot | Support 512G Micro SD Card Slot |
| RS485 | N/A |

| | |
|-----------------------|------------------------|
| General | |
| Housing | Metal |
| Anti-cut Bracket | NO |
| IR Cut Filter | NO |
| Operation Temperature | -20℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%, 350mA |
| Dimension | 36(W) x 36(H) x27(D)mm |
| Weight | 300g |