



## SPECIFICATION

<b>Model NO.</b>	<b>MAMR32DP</b>
<b>System</b>	
Main Processor	Quad Cortex A53
Operating System	Embedded LINUX
<b>Video</b>	
Input	32CH(4000*3000,3840*2160,2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720, etc)
Output	1*HD,1*VGA
<b>Audio</b>	
Input	1 Port RCA, support 32CH IPC audio input
Output	1 Port RCA(Linear, 1kΩ), HD output
Audio Bit Rate	64kbps
Audio Compression standard	G711U, G711A, AAC
Intercom	support (two-way)
<b>Alarm</b>	
Sensor Input	4CH
Output	1CH
Motion Detection	32Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output
<b>Display</b>	
HD Output1	4K(3840*2160), 2560*1440,1920*1080, 1280*1024, 1280*720, 1024*768
HD Output2	N/A
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Display Split	36CH/25CH/17CH/16CH/13CH/10CH/9CH/8CH/6CH/4CH/1CH
Digital Zoom	YES
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
<b>Recording</b>	
Video Compression	H265/H264/H265+/H264+
Resolution	12MP(4000*3000),8MP(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1(720×576/720×480)
Record Rate	PAL :12MP@32CHx25fps,8MP@32CHx25fps,5MP@32CHx25fp,4MP@32CHx25fp,3MP@32CHx25fp,1080P@32CHx25fp, 960P@32CHx25fp,720P@32CHx25fp, D1@32CHx25fp NTSC: 12MP@32CHx30fps,8MP@32CHx30fps,5MP@32CHx30fp,4MP@32CHx30fp,3MP@32CHx30fp,1080P@32CHx30fp, 960P@32CHx30fp, 720P@32CHx30fp, D1@32CHx30fp
Record Mode	Manual\Timer\Motion Detection\ Alarm\Smart Event
<b>Playback &amp; Backup</b>	
Local Sync Playback	3CH 12MP@30fps,4CH 8MP@30fps,6CH 5MP@30fps,8CH 4MP@30fps, 16CH 1080P@30fps, 16CH 960P@30fps, 16CH 720P@30fps,16CH D1@30fps
Decode Capability	1080P(1920x1080)@480fps

Remote Sync Playback	YES
Search Mode	ALL, Timing Video, Motion Detection, Alarm,Tag search,Smart Event,Pictrue,Log
Playback Functions	Play, pause, fast forward, rewind, previous frame, next frame, electronic zoom, clip, audio
Backup Mode	USB Device/Network

## Network

Interface	1xRJ45 10M/100/1000MAdaptive Ethernet Interface
Incoming Bandwidth	320Mb
Network Functions	IPv6,TCP/IP, HTTP,HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p,PPPOE
Onvif	onvif S,onvif T
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Cloud Support	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	N/A
WIFI	N/A

## Storage

Interface Type	2 SATA Hard Disk Interface (3.5" SATA)
Capacity	Up to 10 TB capacity for each HDD
eSATA	N/A

## General

Language UI	Simplified Chinese,Traditional Chinese, English, Polski,Russian,Deutsch, French, Portuguese, Spanish, Italian, Korean, Japanese,Ukrainian
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
RS485	N/A
Power consumption	DC12V/4A ≤15W (Without Hard Disk)
Working Environment	-10℃~50℃, 10%~90%(humidity)
Dimension(W×D×H)	380 x 316 x 51mm
Weight	2.71kg≤ kg(without HDD)