

XS-NVR3108-4K8P-1FACE



X-Security NVR for IP cameras
8 CH IP video and 8 PoE ports
Maximum recording resolution 12 Mpx
1 CH facial recognition
2 CH human and vehicle recognition
Compression H.265+



X-Security
NVR for IP cameras
8 CH
80 Mbps bandwidth supported
Maximum resolution 12 Megapixel
1 CH facial recognition
2 CH perimeter protection with human and vehicle classification
Compression H.265+/H.265/H.264+/H.264/MJPEG
8 PoE ports IEEE802.3af
VGA and HDMI 4K output
Mouse
Space for 1 HDD
WEB, CMS (DSS/PSS), Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	X-SECURITY
Inputs for IP cameras	8 channels
Video outputs	1 HDMI 4K, 1 VGA
Bidirectional audio	1 RCA input, 1 RCA output
Video compression format	H.265+/H.265/H.264+/H.264/MJPEG
Video analysis	IVS: Line Crossing Area Intrusion Face Detection Face Detection
Facial recognition	1 live analogue face comparison channel
Intelligent motion detection	Up to 2 channels capable of classifying targets amongst humans and vehicles
Total bandwidth	80 Mbps
Recording resolution	12Mp, 8Mp (on 1 channel), 6Mp, 5Mp, 4Mp, 3Mp, 1080P (on 4 channel), 720P, D1...
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Recording method	Manual, programmed, motion detection
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA internal interface
Internal memory	1 SATA HDD 3.5" of up to 8 TB (not included)
Communication	2x USB 2.0 (Mouse and backup) / 1 RJ45 10/100M (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12 V / 1.5 A / PoE IEEE802.3af
Dimensions	1U, 48 (H) x 260 (W) x 225 (D) mm / 0.8 Kg (without HDD)