

IP CCTV / Professional IP cameras / Uniview - Uniarch / Speed Domes

UV-UHO-P1H-M3F4D

Uniarch



Features

- Uniarch
- IP PT camera
- 3 MP (2304x1296)
- 4 mm Lens
- Minimum illumination 0.005 Lux | 0 Light with supplementary lighting
- IR range 30 m | White light range 10 m
- Autotracking
- Built-in microphone
- Built-in speaker
- Digital WDR
- Wifi IEEE802.11b/g/n
- Slot for MicroSD card up to 512 GB
- Weatherproof IP66

Specifications

Brand	Uniarch
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Lens	4 mm
Main Stream rate	3MP (2304 x 1296), Max 20fps;
Extra Stream rate	640 x 360, Max 20fps;
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.005 lux (F2.1 AGC ON) 0 lux with IR on
Infrared range	30 m
White light range	10 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio	Microphone and speaker incorporated
Detection functions	Motion detection, Ultra motion detection, audio detection
UMD	Support
Autotracking	Support
Wi-Fi	IEEE802.11b/g/n
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	IP66

Dimensions

Ø118 x 118 x 199 mm

Weight

530 g