

UV-UHO-S3S-M33F36D

Uniarch



Features

- Uniarch
- PT IP Dome Camera
- 1/2.8" Progressive Scan CMOS
- 3 Megapixel (2304x1296)
- Panoramic lens 2.8 mm and PT 6 mm
- IR range of 10 m
- White light range 10 m
- Ultra compression H.265/H.265/H.264
- WiFi IEEE802.11b/g/n/ax
- RJ-45 10/100 BaseT
- Ultra Motion Detection (UMD)
- Pedestrian/Motor Vehicle/Pet Detection
- Loud sound detection
- Cry detection
- Includes Microphone and Speaker
- MicroSD card slot up to 512 GB
- WEB, CMS, Smartphone and NVR interface
- 5 V / 1.5 A
- USB Type-C interface

Specifications

Range	Uniarch
Image sensor	1/2.8" Progressive Scan CMOS
Day / Night	Mechanical ICR filter
Maximum resolution	3 Megapixel (2304x1296)
Lens	Fixed: 2.8 mm (Panorama) PT: 6 mm (Detail) (Dual lens is equivalent to a single IP address and occupies 2CH of video on an NVR)
FOV	Panorama: Horizontal: 109.2° Vertical: 57.9° Diagonal: 117.8° Detail: Horizontal: 55.1° Vertical: 29.3° Diagonal: 62.6°
Range performance	Panorama: D: 51.4 m O: 20.6 m R: 10.3 m I: 5.1 m Detail: D: 110.2 m O: 44.1 m R: 22 m I: 11 m
Main Stream rate	3MP (2304*1296)@15fps 2MP (1920*1080)@15fps 720P (1280*720)@15fps
Extra Stream rate	640*360@15fps 2CIF(704*288)@15fps CIF(352*288)@15fps
Compression	Ultra H.265/H.265/H.264
WDR	DWDR
WIFI	2.4G Wi-Fi IEEE802.11b/g/n/ax
Infrared range	10 m
White light range	10 m
PT Range	Pan 0° ~ 355° Tilt -15° ~ 90°
Internal memory	MicroSD card slot up to 512 GB
Intelligent detection	Human, vehicle, pet, baby crying and loud noise detection.

Alarms	Does not have
Audio	Includes microphone and speaker
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 5 V / 1.5 A USB Type-C
Led indicator	1, Red / Blue
Temp. operation	-10° C ~ 50° C
Dimensions	Ø80 x 127 (h) mm