

XS-IPD842SWHA-8U-AI

X-Security IP Dome Camera
8 Megapixel (3840x2160)
Lens 2.8 mm Starlight Range ULTRA
IR LED 30m | WDR
WizSense, False Alarm Filter
Alarm | Audio



X-Security
IP camera
ULTRA Range
1/2.8" Progressive CMOS
8 Megapixel (3840x2160)
2.8 mm Lens
High sensitivity Starlight
0.007 Lux
IR Array Range 30 m
WizSense, false alarm filter for humans and vehicles in line crossing and area intrusion
WDR
IR Cut
Alarm
Audio
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP67
Vandal proof IK10
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/2.8" Progressive CMOS
Maximum resolution	8 Megapixel (3840x2160)
Main Stream rate	3840 × 2160 @(1~20 fps) 3840 × 2160 @(1~25 fps)
Extra Stream rate	704x576 (1 ~ 25 FPS), 704x480 (1 ~ 30 FPS)
Compression	H.265+/H.265/H.264+/H.264
Lens	2.8 mm (H: 108°)(V:58°)
Minimum illumination	0.007 Lux (Colour)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR, BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
WizSense	False Alarm Filter for human and vehicle crossing line and intrusion in area
Video analysis	Line crossing Area intrusion
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Alarm	1 Input / 1 Output
Audio	1 Input / 1 Output
External storage	256 GB microSD card slot
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Power	DC 12 V / 225 mA / 2.7W max, PoE IEEE802.3af 3.6W max
Temp. operation	-40° C ~ +60° C
Degree of protection	Waterproof IP67, Anti-vandal IK10
Dimensions	81 mm (D) x 110 (Ø) mm
Weight	378 g