

XS-IPT987SWHA-8U-AI

8 MP IP Camera
1/1.8" Progressive Scan CMOS
Ultra Low Light
2.8 mm Lens
Alarm | Audio
Perimeter Protection: False alarm filter



X-Security
IP Turret Camera
ULTRA Range
1/1.8" Progressive Scan CMOS
8 Megapixel (3840x2160)
2.8 lens
Starlight
0 Lux
IR range 30m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE IEEE802.3at
WDR
3D-DNR
IR Cut
Wizsense, false alarm filter for vehicles and people
SMD Plus: enhanced motion detection
SD card recording
Alarm
Audio
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Weatherproof IP67

Specifications

Brand	X-Security
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840x2160)
Minimum illumination	0.007 Lux / F1.4
Infrared lighting	0 Lux / Matrix LED IR (30 m)
Lens	2.8 mm Horizontal 108° x Vertical 58° x Diagonal 127°
Compression	H.265+ / H.265 / H.264
Video Bit Rate	3 Kbps ~ 8 Mbps
Main Stream rate	8Mpx / 6Mpx / 5Mpx (1~20 FPS), 4Mpx / 3Mpx / 1080p / 1.3Mpx / 720p (1 ~25 FPS) / D1 / VGA /CIF
Extra Stream rate	704x576 / 704x480 (1 ~ 25 FPS)
Image improvements	WDR, BLC, 3D-NR, MD, Privacy Mask, ROI
Day / Night	Auto / Programmable / Colour / BW (Black and White)
Advanced features	Wizsense, false alarm filter for vehicles and people Crossing of line Intrusion
Motion Detection	SMD Plus enhanced motion detection with filter for people and vehicles
Internal memory	SD card (up to 256 GB)
Network interface	Ethernet 10/100 BaseT
Alarms	1 IN / 1 OUT
Audio	1 IN / 1 OUT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 2.6W / 210 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-40° C ~ +60° C
Dimensions	69 Ø x 93.6 (H) mm
Weight	530 g