

# XS-NVR2108-4K8P

X-Security NVR for IP cameras  
8 CH IP and 8 PoE ports  
Maximum recording resolution 8 Mpx  
Compression H.265 / H.264  
Outputs 4K HDMI & VGA  
Supports 1 hard disk



X-Security  
NVR for IP cameras  
8 CH  
80 Mbps bandwidth supported  
Maximum resolution 8 Megapixel  
Compression H.265 / H.264  
VGA and HDMI 4K output  
IP Dual Stream Access  
Mouse  
Space for 1 HDD  
8 PoE ports IEEE802.3af/at  
WEB, CMS (DSS/PSS), Smartphone and NVR interface  
ONVIF Compatible

# Specifications

<b>Brand</b>	X-SECURITY
<b>Inputs for IP cameras</b>	LAN port up to 8 channels
<b>PoE</b>	Switch of 8 PoE channels IEEE802.3af/at
<b>IP compatible cameras</b>	X-SECURITY (proprietary protocol), HIKVISION, SAFIRE, ONVIF
<b>Video outputs</b>	1 HDMI 4K, 1 VGA
<b>Bidirectional audio</b>	1 input, 1 output, RCA
<b>Video compression format</b>	H.265 / H.264
<b>Display resolution</b>	3840x 2160, 1920x 1080, 1280x 1024, 1280x 720, 1024x 768
<b>Total bandwidth</b>	80 Mbps
<b>Recording resolution</b>	8Mp, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 720P, D1...
<b>Simultaneous multifunction</b>	Pentaplex: Live, Recording, Playback, Backup and Remote Access
<b>Alarms</b>	No
<b>Recording method</b>	Manual, programmed, motion detection
<b>Backup</b>	USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA internal interface
<b>Internal memory</b>	1 SATA HDD 3.5" of up to 6 TB (not included)
<b>Communication</b>	2x USB 2.0 (Mouse and backup) / 1 RJ45 10/100M (Ethernet)
<b>Remote access</b>	Browser (ActiveX), mobile app or softwarePSS
<b>Power</b>	DC 48 V / 1.25 A
<b>Dimensions</b>	1U, 48 (H) x 260 (W) x 225 (D) mm / 0.8 Kg (without HDD)