

SW1008-GF-120-HIPOE

PoE Switch

8 PoE ports + 1 Uplink + 1 GIGA SFP

Port speed 10/100/1000 Mbps

Port 65W 1 / ports 30W 2-8 /

maximum 120W

HD mode that optimizes CCTV

transmission

Hi-PoE / IEEE802.3at (PoE+) / af

(PoE)



Desktop Switch

8 ports RJ45 10/100/1000 Mbps + 1 Uplink + 1 SFP Gigabit

Supports PoE power supply up to 120W in total for all ports

Up to 65W in port 1

Compatible with PoE IEEE802.3af/at and Hi-PoE

HD mode that optimizes CCTV transmission

Specifications

Interface	8 PoE ports RJ45 10/100/1000 Mbps + 1 Uplink Gigabit + 1 SFP Gigabit
Port speed RJ45	8x 10/100/1000M - 1x 10/100/1000 Mbps
SFP port speed	1x Gigabit
Power supply	Up to 65W (Hi-POE) in port 1 and up to 30W in ports 2 to 8 (120 W in total for the switch)
PoE features	Hi-PoE / IEEE 802.3at PoE+ / IEEE 802.3af PoE
HD Mode	Optimizes CCTV transmission
Smart PoE	PoE Watchdog - Progressive protected start
Power	AC 220 V
Operating temperature	-40° C - 55° C
Dimensions	200 (D) x 40 (H) x 155 (W) mm