

How to Connect a WiFi Camera to WiFi NVR Advanced

Description

This shows you how to connect a WiFi Camera to WiFi NVR.

Prerequisites

- A WiFi Camera
- A WiFi NVR

Step by Step Instructions

Note: These instructions only apply for WiFi NVRs and Cameras.

1. Connect the NVR and IP Camera directly to your router, switch, or modem with a CAT5 cable.

2. Open the ConfigTool and locate your NVR and IP Camera.

3. Login to both using Internet Explorer. We will open these on two separate tabs. These two IP networks, one wireless and the other wired, will have the following ip scheme for this test:

- NVR Wired IP: 172.16.13.106
- NVR Wireless IP: 11.1.1.1 (SSID: NVR2.4G)
- Camera Wired IP: 172.16.13.108
- Camera Wireless IP: 11.1.1.108

4. Configure the NVR via the Settings->Network->WIFI AP menu, here is all of the information that you will need for addressing wireless cameras. The wireless NVR's AP is hosting the network much like a router, to configure the IP address/default gateway use the IP Config area. For addressing the Wifi Camera's to an IP address the DHCP Server section will allow you to specify a range withing your default gateway. We will use the default of 11.1.1.(100-200).





5. Configure the Camera via the Setup->Network->TCP/IP and select the wireless Ethernet card.



6. Select DHCP, or Configure the IP address to match the Default Gateway and Subnet mask configured in step 4, then enter in an IP within the DHCP range. For this example we will use our designated IP address from step 3 (11.1.1.108). Then select Save.





7. Navigate on the Camera to Setup->Network->WiFi, this is the menu that needs to be used to connect the device to the Wireless NVR AP's SSID of NVR2.4G. Select Add SSID and enter the password and select connect, or if the SSID is hidden Manually add the SSID and password. Select refresh to see if you have connected to the AP. After this the Wireless camera has been connected to the AP, but not added to it's devices yet.

alhua				Live	Playback	500.0	Alami	ogout
Camera Network	WFI Z Dada DGA	WP9					66 5540] [Search	5580
Connection Intry: Const Const Introduce	0 0 0 0 0	CVCD CRUMEL NVM2.40 DH-Report DH-Report dahar_vit HP-Pres ST-Offungt DHC-WARDACK	Connect To NVR240 Signal Daality Authentication Manue Input Present Contro NG	et N errat Pok Ales error dene Ales	E Vervor	Construction Note Construction Construction Construction Construction Construction Construction Construction Construction Construction Construction		· · · · · · · · · · · · · · · · · · ·
www. owar to Card Exotest Exotest Stotest Stotest System	Will Lafo SSID IF Address Subwell Mask Outerway	NVTIC-40 consected 1111138 265,265,255,0 11111	l					

8. Navigate on the wireless NVR to the SETTING->CAMERA->REGISTRATION menu, here is where you can see devices that are connected via wireless and on the wired network. If you see your camera here select the green plus sign to add it, make sure you have the appropriate login information. If you cannot see your camera here please select



the manual add button and input the camera's appropriate login information and select Save.

too have	Preview	Playback	Atarm	SETT	NG INF	0 Logout			
0	REGISTRATION						- S-		
CATION .	Device Search								
	Barrow	(A)	Status	Note		IP Address	Addbet	Type	M ALL
ĸ	1	-	-			11.1.1.000	+	9	
						02.010.010			2
6		12	12			172 55 13 194	+	-	1
	4	-				172 96 13 227	+		1
	1 2	Manual Add				53	*		4
		Martin			10				100
	1.1		interest in the second				1		5
	1	Protocol	PTup		-		1		5
	10	IP Address	11.1.1	105					1
	11	TCP Put :	3777	h-	(3-05535)		+		2
	12	User Name	admir				+		2
	13	Destant					+		2
	14		10 (10 (10 (10 (10 (10 (10 (10 (10 (10 (100		+		1
	15	Decode But	for Defaul	10)	~		+		2
	-10	Channel	1		~		+		2
	17				and I		+		2
	10			and a state	Cancel		+		1
	19	L		-			*		1
	20					1/2/10/10/121	+		1
1	-								

9. After the camera is added you might need to wait for the video feed to cache, select the Refresh button to make sure the Status indication is GREEN and not RED.

	Preview.	Playback	Alaren	SETTING	INFO Logout			
ACI I	REGISTRATION		Wit:	-98 3M	a	11		
RATION	Contra Tanan							
	France Search	<u> </u>						
	-		Status	Name	P Address	Address	Titlet	Modify
n.	1.1.1	1	香	IFC .	11.1.1.100	0	*	1
en l					1000000	17.0		14.1
RAGE TEM	3		-		172, 16, 13, 194	+		1
	4	-	1.5	-	172.16.13.227			1
	5	-	-	100	172.16.13.34	+		1
		<u>_</u>	2.0		172, 58, 13, 108	+		
	1				172 16 13 5	+		1
				(m)	172 16 13 17	· •		1
		-	-		172.16.13.132	*		1
	10	-	-	+	172 16 13 133	+		24
	.11	-			\$72.46.83.32	+		2
	12	-		-	172 16 13 11	+		1
	- 13	(.e.			172,16.13.33	+		
	14				172.46.13.27	+		1
	15	-	-	-	172.56.13.119			1
	16	-			172.96.13.102			1211
	17	17		1.00	172.56.33.179	+		1
	- 10	1.00	7.44		172, 16, 13, 194	· · · · ·		1
	13	1.0	1.0		172.10 13.95	+		2
	20		1.0	1.00	172, 95 13 121	· · · · · · · · · · · · · · · · · · ·		100
		Section 1. Sector 1.			203.88,43.484			

10. Select Preview and then the Camera that was added to ensure the stream is running correctly. At this time you can disconnect the wireless camera from the wired network and install it where there is wireless coverage.



