

IP CCTV / Professional IP cameras / X-Security / Dome Cameras

XS-IPD842A-4P-DL-WIZ

X-SECURITY



Features

- X-Security
- IP Dome Camera with Dual Light
- PRO Range
- 1/2.9" Progressive CMOS
- 4 Megapixel (2688×1520)
- 2.8mm lens
- 0.006 Lux
- Dual Light: IR30m + 30m White LED
- Compression H.265+/H.265/H.264+/H.264
- RJ-45 10/100 BaseT
- SMD Plus
- IVS WizSense: classification of human and vehicle
- Intelligent search
- Built-in microphone
- WDR 120dB
- IR Cut
- MicroSD up to 256GB
- PoE IEEE802.3af
- Weatherproof IP67
- ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/2.9" CMOS image sensor
Maximum resolution	4 Megapixel (2688 × 1520)
Lens	2.8 mm (H: 102°; V: 54°; D: 121°)
Main Stream rate	2688 × 1520@(1–20 fps)/2560 × 1440@(1–25/30 fps)
Extra Stream rate	704 × 576@(1–25 fps)/704 × 480@(1–30 fps)
Compression	H.265; H.264; H.264H; H.264B; MJPEG
Minimum illumination	0.006 lux@F1.6 (Colour, 30 IRE) 0.0006 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
Dual Light	Detection modes: Intelligent Mode (By default, IR activated and switches to white LED in the presence of a target) IR mode
Range performance	63.6 (D), 25.4 (O), 12.7 (R), 6.4 (I)
Video bit rate	H.264: 32 kbps–6144 kbps H.265: 12 kbps–6144 kbps
Image improvements	WDR (120 dB), BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
Network interface	Ethernet 10/100m BaseT
Audio	Built-in microphone
Audio Compression	G.711a; G.711Mu; G.726; PCM
External storage	256 GB microSD card slot
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF (Profile S/Profile G); .CGI; P2P
Power	DC 12 V / 2.5 W, PoE IEEE802.3af
Temp. operation	-40° C ~ +60° C
Material	Metallic
Lens Adjustment	3 Axis



Color	White
Degree of protection	Waterproof IP67, Anti-vandal IK10
Dimensions	81 mm (D) x 109.9 (Ø) mm
Weight	350 g