

IP CCTV / Professional IP cameras / X-Security / Turret cameras

XS-IPT981A-4P-SL-WIZ

X-SECURITY



Features

- X-Security
- IP Turret camera with active deterrence
- PRO Range
- 1/2.9" Progressive CMOS
- 4 Megapixel (2688×1520)
- 2.8mm lens
- 0.004 Lux
- IR60 m
- Compression H.265+/H.265/H.264+/H.264
- RJ-45 10/100 BaseT
- SMD Plus
- IVS WizSense: classification of human and vehicle
- Intelligent search
- Built-in microphone
- Audio
- WDR 120dB
- IR Cut
- MicroSD up to 256GB
- Active deterrence with loudspeaker and police light
- PoE IEEE802.3af
- Weatherproof IP67
- ONVIF Compatible

Specifications

Brand	X-SECURITY
Maximum resolution	4 Megapixel (2688x1520)
Image sensor	1/2.9" Progressive CMOS
Lens	2.8mm (H: 101.6°; V: 54.8°; D: 122.1°)
Main Stream rate	2688x1520@(1–20 fps) / 2560x1440@(1-25/30 fps)
Extra Stream rate	704 × 576@(1–25 fps) / 704 × 480@(1–30 fps)
Compression	H.265; H.264; H.264H; H.264B; MJPEG
Range performance	64-210 (D), 25.6-84 (O), 12.8-42 (R), 6.4-21 (I)
Minimum illumination	0.004 lux@F1.0 (Color, 30 IRE) 0.0004 lux@F1.0 (B/W, 30 IRE) 0 lux (Illuminator on)
Dual Light	Detection modes: Intelligent Mode (By default, IR activated and switches to white LED in the presence of a target) IR mode White LED mode
IR range	30 m (IR) 30 m (White light)
Image improvements	WDR 120 dB, BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
SMD Plus	Yes (Human and vehicle based motion detection)
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
Intelligent search	Using microSD card or NVR X-Security
Active deterrence	Red and blue LED flash / Audible warning Triggered by an artificial intelligence event
Network interface	Ethernet 10/100M BaseT
Audio	1 Input / 1 Output / Built-in microphone / Speakerphone
Audio Compression	G.711a; G.711Mu; PCM; G.726
Remote access	WEB, CMS (Smart PSS Lite / DSS / DMSS), Smartphone and NVR interface
Material	Metallic
Interoperability	ONVIF (Profile S/Profile T); CGI
Power	DC 12 V / 3W, PoE IEEE802.3af



Temp. operation	-40° C ~ +60° C
Degree of protection	Weatherproof IP67
Dimensions	109.9 (?) x 103.5 (H) mm
Weight	390 g