

Lite series |



H.264+/H.264 codec decoding
Max 80Mbps incoming bandwidth

• Support IPC UPnP, 4PoE ports

Up to 6Mp resolution preview&playback
 HDMI/VGA simultaneous video output

3D intelligent positioning with Dahua PTZ camera

6 Megapixel nvr 4 Channel Smart 1U 4PoE Lite Network Video Recorder

CAMERA SHOP 24

System Overview

Dahua's NVR is one of the NVRs which have the most reasonable price and best quality for IP video surveillance applications. This Lite series NVR provides up to 6MP resolution. It supports smart H.264 decoding, save up to 70% HDD space and storage. Additionally, the NVR features a mouse shortcut operation menu, remote management and control, centre storage, edge storage, and back up storage.

Designed as a low-cost, easy installation, this NVR is ideal for a wide range of applications such as home safety, grocery, wharehouse, education, and financial institutions.

The NVR is compatible with numerous third-party devices making it the perfect solution for surveillance systems with or without a video management system (VMS). Its open architecture supports multi-user access and is compatible with ONVIF 2.4, enabling interoperability when combined with IP cameras.

Functions

Smart H.264+

Delivering high quality video without straining the network, Smart H.264+ is the optimized implementation of H.264. The Smart H.264+ encoding platform includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing a savings of up to 70% of bandwidth and storage when compared with standard H.264.

Plug & Play

With the Smart Add function, the installation of IP system is as easy as an analog system, no matter the NVR with or without a PoE switch embedded. It should be noted that the NVR has to be in the same router as cameras.

ANR (Automatic Network Replenishment Technology)

Video record in SD card in IP cameras when the network breaks down, and after the network recovered, the video will be transferred to NVR and then recorded in it. Easy4ip

You can monitor at anytime and anywhere with Easy4ip. There are two modes Easy4ip web client and mobile app. With this function, you can manage your devices more convenient.

www.dahuasecurity.com



Technical Specification

System

	Main Processor	Dual-core embedded processor		Network
	Operating System	Embedded LINUX		Interface
	IP Camera Input	4 Channel		Ethernet Port
	Two-way Talk	1 Channel Input, 1 Channel Output, RCA		PoE
	Interface	1 HDMI, 1 VGA		T OL
	Resolution	1920×1080, 1280×1024, 1280×720, 1024×768		Network Fund
	Multi-screen Display	1/4		Optical Fiber
	OSD	Camera title, Time, Camera lock, Motion detection, Recording		Max. User Ac
	Compression	H.264+/H.264		Smart Phone
	Resolution	6Mp/5Mp/4Mp/3Mp/1080P/ 720P/ D1&etc.		Interoperabili
	Record Rate	80Mbps		Storage
	Bit Rate Record Mode	16Kbps ~ 20Mbps Per Channel		Internal HDD
				HDD Mode
		Manual, Schedule(Regular(Continuous), MD, Stop		eSATA
	Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		В
	Audio and Video		DC	232
	Display		1.52	232
	Recording		RS4	185

	Third-party Support		Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic Pelco, Samsung, Sanyo, Sony, Videotec, and more			
	Network					
	InterfaceEthernet PortPoENetwork FunctionOptical Fiber InterfaceMax. User AccessSmart PhoneInteroperability		1 RJ-45 port (10/100Mbps)			
			1 Independent 100Mbps Ethernet Port			
			4 ports (IEEE802.3at/af)			
			HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search(Support Dahua IP camera, DVR, NVS and etc.), Easy4ip			
			N/A			
			128 users			
			iPhone, iPad, Android			
			ONVIF 2.4, CGI Conformant			
	Storage					
	Internal HDD HDD Mode		1 SATA III Port, up to 6TB capacity for each HDD			
			Single			
	eSATA		N/A			
US	USB 2 p		orts (2 Rear USB2.0)			
RS	RS232		۱.			
RS	RS485		N/A			

Third-party Support

Auxiliary Interface

Video Detection and Alarm Electrical

Trigger Events	Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips		Power Supply		Single, DC48V/1.25A	
Video Detection	Motion Detection, MD Zones: 396 (22 × 18),		Power Consumption		<4W (without HDD)	
Alarm input	and Tampering		Operating Conditions		10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa	
Aummput			Storage Conditions		0°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH	
Relay Output	N/A	-20		20	0 C +70 C (*** + +130 F), 0 50% KH	
Sync Playback	1/4		Dimensions(W×D×H)		Smart 1U, 204.6mm×204.6mm×45.6mm (8.1" x 8.1" x 1.8")	
Search Mode	Time /Date, MD and Exact Search (accurate to second)		Net Weight		0.45kg (0.99 lb) (without HDD	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera,		Gross Weight		1.5kg(3.31 lb)(without HDD)	
	Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	Environmental				
Backup Mode	USB Device/Network					

Playback and Backup Construction

Certifications

CE	EN55032, EN55024, EN50130-4, EN60950-1
FCC	Part 15 Subpart B, ANSI C63.4-2014

www.dahuasecurity.com



Ordering Information					
Туре	Part Number	Description			
4 Channel NVR	DHI-NVR	4 Channel Smart 1U 4PoE Lite Network Video Recorder			
Accessories	N/A	N/A			
Dimensions (mm)					

204. 6





