

Dome camera Range 5Mpx/4Mpx

PRO

4 in 1 (HDTVI / HDCVI / AHD / CVBS)

1/2.7" SmartSens©

3.6 mm Lens

IR LEDs Array Range 30 m

Weatherproof IP66



HDTVI, HDCVI, AHD and Analogue dome camera

PRO Range

1/2.7" SmartSens 5.0 Megapixel

5Mpx (HDTVI) / 4Mpx (HDCVI)

Output 4in1

3.6 mm Lens

0 Lux - IR Array Range 30 m

2DNR

IR Cut

Weatherproof IP66

Specifications

Range	5Mpx/4Mpx PRO
Image sensor	1/2.7" SmartSens®
Resolution	Standard: 4Mpx@25FPS (HDTVI, HDCVI, AHD) Optional via menu: 5Mpx@20FPS (HDTVI, AHD)
Video output	1 x BNC switchable HDTVI 2.0 / HDCVI / AHD / CVBS
Minimum illumination	0 Lux / 2 IR LEDs Array (30 m)
Basic functions	OSD menu, Day/Night with IR-CUT (ICR)
Configurable OSD functions	AE, 2DNR, AWB
Lens	3.6 mm
Power supply	DC 12 V / 300 mA max.
Degree of protection	Weatherproof IP66
Temp. operation	-10° C ~ +50° C
Dimensions	70 (He) x 94 (Ø) mm
Weight	300 g