



720P speeddome camera

Camera

Image sensor: 1/3 inch CMOS
Effective pixels: 1280(H) x 720(V)
Horizontal resolution: 720P/30,720P/25
Min. illumination color: 0.05 Lux/F1.6, B/W: 0Lux/F1.6(IR ON)
Scanning system: Progressive scan
S/N ratio: 50Db
White balance: Auto / Manual / Day
Day&Night: Auto, COLOR, B/W(ICR)
Electronic shutter: AUTO / MANUAL
Image rotation: Off / H-Rev / V-Rev
AGC: x1/x2/x4/x8/x12/x16/x24/x32/x64
BLC: OFF / BLC
DWDR: OFF / ON

Lens

Zoom: 18X optical zoom
Focal length: f=4.7 to 84.6mm(F1.6~F2.7)
Focus: Auto/Manual
Iris: Auto / Manual

Function

Network protocols: HTTP, SMTP, DHCP, DNS, DDNS, NTP, FTP, Qos, TCP, HTTPS, IGMP
Dual-stream: Support
Network interface: Build-in RJ45, support 10M/100M network data
ONVIF: Standard Protocol (Onvif)
Webbrowser: Support IE7
Client: Support
Horizontal: 360° Endless
Vertical: 0°~90° Auto rotation

Pan / Tilt speed manual: 150°/sec, Preset:200°/sec
Preset: 256 Preset
Preset accuracy: 0.1°
Cruise: 6
Auto scan: Support
Power up action etc: Support
Home function: Preset/Auto Pan/Cruise
IR irradiation distance: 100M
IR irradiation angle: Adjustable by zoom
Communication: RS-485
Protocol: Pelco-D,/Pelco-P
Address: 0-255
Software add: Support
Privacy zone: 4 zones
Alam input: N/A
Alarm linkage: N/A
OSD menu: English/Chinaese

Environment

Power supply: DC12V 4A
Power: 35W
Operating temp: -30C~60C
Humidity: 0%~90%
Size: 272(H)*190(D)mm
Application environment: Outdoor
Waterproof: IP66
Weight: 3.3KG