

5n1 DVR

4 CH HDTV / HDCVI / AHD / CVBS /

2 IP

4K/5 Mpx/3Mpx

Alarms (4/1) | 4 CH audio

HDMI 4K, VGA and BNC (CVBS)

output

Supports 1 hard disk



DVR 5n1

4Ch video HDTV/HDCVI/AHD/CVBS / 2 IP (extra) / 4Ch audio

H.265+/H.265/H.264+/H.264

Resolution per channel: 4K (10FPS) on TVI or 5Mpx (20FPS) or 3Mpx (18FPS) or 4Mpx/1080p (25FPS) in the rest of HD technologies

PTZ Control (RS485/Coaxial)

Alarms

HDMI 4K, VGA & CVBS Outputs

Mouse

Space for 1 HDD

# Specifications

|                            |   |
|----------------------------|---|
| Video format               | HDTVI / HDCVI / AHD / CVBS / IP   |
| Video inputs               | 4 Channels BNC, (HDTVI / HDCVI / AHD / CVBS)  |
| Hybrid configuration       | 4 Channels from BNC and 2 Channels IP (4K)  |
| Video outputs              | 1 HDMI 4K, 1 VGA, 1 BNC (CVBS) Independent  |
| Audio inputs               | 4 Channel RCA   |
| Audio outputs              | 1 Channel RCA   |
| Bidirectional audio        | Reusing the audio input/output  |
| Video / audio compression  | H.265+ / H.265 / H.264+ / H.264   G.711u  |
| Display resolution         | 4K (3840x2160, 2K (2560x1440), 1920x1080, 1280x1024, 1280x720, 1024x768                                 |
| Recording resolution       | 4K on TVI / 5Mpx / 4Mpx / 3Mpx / 1080p / 720p   |
| Main Stream coding         | 4K (10FPS) on TVI / 5Mpx (20 FPS) / 3Mpx (18 FPS) 4Mpx / 1080p / 720p / VGA / WD1 / 4CIF / CIF (25 FPS) |
| Extra Stream coding        | WD1 / 4CIF / CIF (25 FPS)   |
| Simultaneous multifunction | Pentaplex: Live, Recording, Playback, Backup and Remote Access  |
| Alarms                     | 4 inputs / 1 relay  |
| Video analysis             | VCA: Line crossing   Area intrusion   |
| Recording method           | Manual, programmed, motion detection, alarm   |
| Backup                     | USB (Memory, HDD, CD-RW, DVR-RW) / Network  |
| Internal memory            | 1 HDD SATA 3.5" of up to 8TB  |
| Communication              | RS485 (PTZ) / 2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet)                               |
| Remote access              | Web browser, Smartphone App and Safire Control Center CMS Software                                      |
| Power supply               | DC 12V / 15W  |
| Dimensions / Weight        | 45 (H) x 315 (W) x 242 (D) mm / 1.5 Kg  |