



IP 1 megapixel pan/tilt camera

Camera

Image Device	1.3 Mega-pixel image sensor
Effective Pixels	1280 x 1024 pixels
Gevoeligheid	1.0V/lux-sec (550nm)
Geluid	44dB
Lens	f:4.3mm / F:1.8

Pan & Tilt

Omhoog	355°
Omlaag	-10~90°
Manual Pan Degree	180°/ second (max)
Manual Tilt Degree	120 °/ second (max)
Preset Points	128 preset points
Camera Tour	16 tours

IP Module

Video Encoder	H.264, MPEG4 and Motion JPEG simultaneously (Tri-encoders)
Video Profile	* 13 profiles simultaneously H.264: SXGA/ VGA / QVGA / QQVGA
Compressie	H.264
Frame Rate	Mega-pixel mode: Up to 15fps for all profiles
video	helderheid, tijd en datum
Streaming	Simultaneously multi-profile streaming Streaming over UDP, TCP, or HTTP

Audio

Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps 3GPP: AMR
Audio Streaming	One-way or two-way
Microfoon	Line level in
Audio Output	Line level out

Network

Supported Protocols	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP,
Security	Paswoord, IP adres controle
Users	20 users
Internet	10/100M auto negotiation

System

Programming	Open API for software integration SDK
Alarm Triggers	Intelligent video motion detection and external input
Motion Detection	10-zone video motion detection Event server: FTP server, SMTP server, Samba server. File upload video clip or snapshot Notification via email, HTTP, and TCP
Alarm Events	Go preset position Go auto tour Audio alerting output
Video Buffer	Pre- and post- alarm buffering

Algemeen

Stroom	12V DC external power adapter
Stroom gebruik	7W max
Power over Ethernet	Built in PoE splitter
Connectors	RJ-45 10BaseT/100BaseTX , DC jack Audio in / Audio out
Indication LED	Two-Color LED
Behuizing	Vandaal bestendig
Temperatuur	0°C to 40°C
Vochtigheid	20% ~ 80% (non-condensing)

Viewing System

OS	Windows® 2000, XP, Vista, Windows 7
Browser	IE 6.0 or latter / Firefox 2.0 or later / Safari
Cell Phone	With 3GPP player
Video Player	VLC, Quick Time, Real Player

Software

Search &
Installation
Easy DDNS

IPWizard-2

DIPS™

64ch. mult-channel supports Tri-decoder

16ch. video playback (simultaneously)

Smart & scable digital zoom. Snapshot and edit

Motion, DI, Scheduler recording

Fast rewind and forward (MPEG4, H.264, MJPEG rewind)

32x24 motion detection grids

Bundled NVR
Program

Smart search (by motion)

Sequential search (frame by frame)

E-MAP

Event schedule setting

Remote server function: Remove live view / Remote playback / Remote
setup

Multi-language support