

4in1 dome camera

High performance CMOS

HDTVI / HDCVI / AHD / CVBS

3.6mm Fixed lens

SMD LED's Range 20m

IP66



HDTVI, HDCVI, AHD and Analogue dome camera

PRO Range

High Performance CMOS

HD 1080P (1920x1080)

Output 4in1

3.6mm Fixed lens

0 Lux

IR SMD Range 20 m

3DNR

ATR

IR Cut

Weatherproof IP66

Specifications

Range	1080p PRO
Image sensor	High Performance CMOS
Resolution	HD 1080p (1920x1080) at 25 FPS
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Minimum illumination	0 Lux / SMD LED's SMD (20m)
Basic functions	OSD menu (remote), Day/Night with IR-CUT (ICR), ATR
Configurable OSD functions	DWDR, 2D/3D-NR, AWB, ATW, HLC, BLC, AGC, AF, Sense-UP,AE, AWB, AGC
Lens	3.6mm fixed lens (D: 76°)
Power supply	DC 12 V / 350 mA
Degree of protection	Weatherproof IP66
Temp. operation	-30° C ~ +60° C
Dimensions	80 (De) x 114 (Ø) mm
Weight	280 g